




















## DIMENSIONS AND BASIC SPECIFICATIONS

	<b>DIMENSIONS</b>	EN ISO 24342	Plank: 146 x 730 mm
	<b>THICKNESS</b>	EN ISO 24346	6 mm (5 mm spc + 1 mm integrated underlayer)
	<b>WEAR LAYER</b>	EN ISO 24340	0,70 mm
	<b>INSTALLATION METHOD</b>		Unizip click-system
	<b>SURFACE TREATMENT</b>		PU coating + protected by aluminum oxide (scratch-resistant) and stain-resistant technology.
	<b>CORE</b>		Sound-absorbing, water-resistant, rigid-core SPC.

## TECHNICAL DATA - CE EN 14041

	<b>BEVELS</b>	MICRO	4 sides
	<b>MASSA</b>		10,15 kg/m <sup>2</sup>
	<b>STANDARD</b>	EN 16511	
	<b>CLASSIFICATION</b>	EN 685 / EN ISO 10874 • Commercial EN 685 / EN ISO 10874 • Housekeeping	34: Commercially demanding 23: Heavy housework
	<b>FIRE RESISTANCE</b>	EN 13501-1	Bfl-S1
	<b>STAIN RESISTANCE</b>	EN 438-2	Group 1/2/3: Degree 5
	<b>UV RESISTANCE</b>	EN ISO 105-B02	> 6
	<b>DIMENSIONAL STABILITY</b>	EN 434 / EN ISO 23999	≤ 0,10 %
	<b>IMPACT NOISE</b>	EN ISO 10140-1	$\Delta L_w = 21 \text{ dB} \cdot \Delta L_{in} = 10$
	<b>ELECTRICAL INCLINATION</b>	EN 1815	OK
	<b>LAST IMPRESSION</b>	EN ISO 24343-1	≤ 0,10 mm
	<b>OFFICE CHAIR TEST</b>	ISO 4918	OK
	<b>THERMAL RESISTANCE</b>	EN 12667	< 0,122 (m <sup>2</sup> K/W)
	<b>SLIP RESISTANCE*</b>	EN 13893 / DIN 51130	DS R9
	<b>WEAR RESISTANCE</b>	EN 660-2 / EN 649	CLASS T
	<b>IMPACT RESISTANCE</b>	EN 13329	OK
	<b>CLICK VOLTAGE</b>	ISO 24334	Short side: 14,7 kn/m • Long side: 3,7 kn/m
	<b>DEGREE OF SWELL</b>	ISO 24336	OK
	<b>FLOOR HEATING</b>	Suitable for STANDARD systems in concrete floors.	Not suitable for electric floor heating.

## HAZARDOUS SUBSTANCES

	<b>VOC EMISSIONS</b>	French / Belgian / German regulations	OK
	<b>FORMALDEHYDE EMISSIONS</b>	EN 717-1	E1
	<b>REACH</b>		Meets the standard
	<b>PCP</b>	EN 12673	OK

\* SLIP RESISTANCE is measured on the product as it leaves the factory. SLIP RESISTANCE may be affected by surface contamination, product use, and maintenance.

© This technical data sheet was prepared by Floorme.

All information, photos, drawings, tables, and graphs in this data sheet are intended to support Floorme's product information and may only be used in connection with the sale, installation, or specification of Floorme products.

Floorme reserves the right to make changes to technical data, specifications, images, and product designs at any time and without prior notice.

The photos and images shown, including the wood selections displayed, are for illustrative purposes only and may differ from the actual product. No rights may be derived from this product sheet.